


MGTP 42 USL-K



For illustrative purposes only

**STAGE 5
CERTIFIED**



GENERAL ENGINE DATA	
Engine brand	KOHLER
Engine model	KDI2504TCR CAC
Cylinders	nr. 4
R.P.M.	rpm 1500
Cubic capacity	cc 2482
Air intake	Turbo
Standard voltage	Vdc 12
Sae	-
BMEP	kPa 684
Cooling	Water
Flywheel P.R.P. Power	kW 42,2
Flywheel Stand-by Power	kW 46,5
Electronic regulator	Yes
Precision class	G2
Oil quantity	l 11,3
EU Stage	STAGE 5

STANDARD FEATURES	
Autostart logic panel DSE 7310 for Manual version	Water / Diesel separator filter
4-poles magnetothermic switch	Central lifting hook
Adjustable ELCB circuit breaker	Doors closing by compression
Power terminal block protection microswitch	Radiator in separate compartment
Oil extraction pump	Heavy duty air filter
Battery disconnect switch	Liquid collection tank with alarm
Mechanical fuel level gauge on tank	Tank inspection flange
3-way valve for diesel circuit from ext. tank (quick couplings excluded)	Reinforced chassis for Rental use
Side rubber bumper protection	Alternator with butadiene protection System 2 Loroy Somer or Total Plus MeccAlte

OPTION factory installed
Kit Sockets: no.1 x 16A 3P 230V + no.2 x 32A 5P 400V with ELCB

GENSET MODEL	
Model	MGTP 42 USL-K
Mechanical version	ULTRA SILENCED version, galvanized and powder-painted canopy, compact base frame, with bunded tank and leak control
Fuel Tank Capacity	l 240
RATED TECHNICAL DATA	
Prime Power (PRP)	kVA 42
Prime Power (PRP)	kW 33,6
Limited Power (LTP)	kVA 46
Limited Power (LTP)	kW 36,8
Rated Power Factor (cos φ)	0,8
Windings	Three phases Series Star
Rated three-phase concatenated voltage	V 400
Rated phase-neutral voltage	V 230
Rated frequency	Hz 50
Fuel type	Diesel
DIMENSIONS	
Length	mm 2300
Width	mm 980
Height	mm 1450
Weight	Kg 1600
FUEL CONSUMPTION	
Fuel Cons. at 100% (L.T.P.)	l/h 12,1
Fuel Cons. at 100% (P.R.P.)	l/h 10,8
Fuel Cons. at 75% (P.R.P.)	l/h 8,3
Fuel Cons. at 50% (P.R.P.)	l/h 5,8
GENERAL ALTERNATOR DATA	
Alternator brand	Leroy-Somer
Alternator model	LSA42.3M7
P.R.P. Power	kVA 45
L.T.P. Power	kVA 49
Winding	Three phases Series Star
Terminals Number	nr. 12
IP Protection	23
Voltage regulator AVR	±0,25% D350 AREP
Short-circuit current	300 %: 10s

SOUND PRESSURE 7m (0% load) dBA 55

STANDARD REFERENCE CONDITIONS
Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. The manufacturer reserves the right to revise the information without notice per our policy of continuous product development and improvement.